



8300

VIBAC® BOPP BOX SEALING TAPE 8300

This Superior Performance packaging tape was designed for carton sealing, splicing, bundling, and other ultra demanding packaging applications. It offers super strength adhesive power in the heaviest applications.

| PROPERTIES | | | |
|--|----------------------------|--|--|
| Total thickness micron | 72.0 micron | Total thickness mils | 2.8 mils |
| Business | Industrial Professional | Industry | Bundling Carton Sealing Splicing |
| Backing Type | BOPP | Backing thickness micron | 50.0 micron |
| Adhesive type | Synthetic Rubber | Color | Clean |
| Tensile strength kg/cm | 8,03 kg/cm | Elongation at break | 200 % |
| Adhesion to steel g/cm | 611,8 g/cm | Rolling ball test (RBT) cm | <2 cm |
| Shear on cardboard | >200 hours | Backing thickness mils | 2.0 mils |
| Tensile strength lb./inch | 45.0 lb./inch | Adhesion to steel oz./inch | 56 oz./inch |
| Rolling ball test (RBT) inch | <0.78 inch | Service Temperature F° (Min / Max) | 30/140 °F |
| Service Temperature C° (Min / Max) | (-2)/60 °C | Application Temperature F° (Min / Max) | 50/110 °F |
| Application Temperature C° (Min / Max) | (10)/43 °C | Available width | 72.0 mm 48.0 mm 36.0 mm 144.0 mm 96.0 mm |
| Available lenght | 914.0 m | Packaging type | jumbo single roll |

8300